

ROOF SHEATHING AS SPECIFIED

ENGINEERED TRUSSES

SOFFIT VENTING AS PER CODE OR AS SPECIFIED

TOP PLATE WITH ANCHOR BOLT AT 600mm o/c OR AS PER CODE

SOFFIT/FASCIA AS PER CODE

CEILING TECHNOLOGY ANGULAR CUT AT EDGE AND SEALED TO WALL WITH NUDURA SPRAY FOAM OR EQUIVALENT

PLASTER BOARD

ATTIC INSULATION AS SHOWN INSTALLED AS PER CODE

PLASTER BOARD

DAMP PROOF MEMBRANE CONTINUOUS UNDER TOP PLATE

NUDURA CEILING TECHNOLOGY

20mmx50mm FURRING STRIP (FACTORY EMBEDDED) 400mm ON CENTRE

NUDURA FORM UNIT

150mmX150mm AIR SHIELD MEMBRANE (CONTINUOUS) LAPPED AND SEALED TO NUDURA FORM

HORZ/VERT REINFORCEMENT AS PER CODE

PLASTER BOARD

RENDER FINISH AS SPECIFIED

DISCLAIMER NOTICE:  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER



# NUDURA

INTEGRATED BUILDING TECHNOLOGY

*Building Value.*

NUDURA FORM UNIT  
MULTI-PURPOSE HANGER  
STANDARD BATT INSULATION  
RENDER FINISH AS SPECIFIED  
ROOF TRUSSES

REV. NO.  
006 KS

DWG NO.

DATE:  
AUGUST 2019

EU-33

DRAWN BY:  
K. STILL

SCALE:  
1 : 8