

NUDURA FORM UNIT

RENDER FINISH AS SPECIFIED

LINTEL REINFORCEMENT AS PER CODE OR ENGINEER DESIGN

38mm MIN. COVER

PROPRIETARY SEALANT BEAD AS SPECIFIED

VERTICAL REINFORCEMENT AS PER CODE OR AS SPECIFIED

PLASTER BOARD

NUDURA LINTEL CLOSURE

DOOR FRAME

DOOR FRAME

DPM ON RENDER BASE AND MESH

EXTERIOR GRADE AND SLOPE AS PER CODE

APPROVED ICF RENDER LAPPED AT DAMP PROOF COURSE

NUDURA TAPER TOP FORM UNIT BELOW DOOR OPENING ONLY

LIQUID OR MEMBRANE DPM OR WATERPROOF CONCRETE

FINISHED FLOOR

NUDURA FLOOR TECHNOLOGY OR EQUIVALENT

FLOOR SLAB

50mm SAND BLINDING

HARDCORE FILL

TRENCH FOUNDATION

DISCLAIMER NOTICE:
 SPECIFIC INFORMATION
 REQUIRED FOR COMPLIANCE
 WITH LOCAL CODES IS THE
 RESPONSIBILITY OF THE
 DESIGNER



STANDARD FORM UNIT DOOR HEAD AND SILL DAMP PROOF COURSE RENDER FINISH AS SPECIFIED	
REV. NO. 000	DWG NO. EU-45
DATE: NOV 2018	
DRAWN BY: K. STILL	SCALE: 1 : 5